

**S800** Ordering code, Accessories

Series S800

**Ordering code**

 Example: **S800 b10/20/40 L**
**Series, Contact configuration**

S800 Form Za SPDT-DB switch with positive opening operation and rigid contact bridge

**Actuator and mounting styles**

| Actuator        | Front mount                               |
|-----------------|-------------------------------------------|
| b Pushbutton    | no mounting brackets                      |
| c Pushbutton    | with mounting brackets                    |
| e Roller lever  | no mounting brackets                      |
| a Roller lever  | with mounting brackets                    |
| as Roller lever | with mounting brackets, slotted holes     |
| d Roller lever  | with mounting brackets, angled on one end |

**Contact material**

|          |
|----------|
| * Silver |
| 10 Gold  |

**Special designs, optional**

Blowouts L

**Actuating and release forces**

 Standard +  
 Stronger reset spring 40

**Terminals**

 M3 screws with saddle clamp +  
 Flat tabs 6.3x0.8 20

**Note:**

This catalogue shows only stock items. For some variants minimum quantities apply. Please ask for the conditions.

**Special variant:**

If you need a special variant of the switch, please do not hesitate to contact us. Maybe the type of switch you are looking for is among our many special designs. If not, we can also supply customized designs. In this case minimum quantities apply.

\* No index

**Accessories**

|        |                                                  |
|--------|--------------------------------------------------|
| SK-100 | Protective housing (half shells) made of PA6     |
| SK-200 | Protective cover made of flexible soft PVC       |
| SK-400 | Protective cap made of glass fibre reinforced PC |

| Parameter                                                                                      | Code                      | Version  |
|------------------------------------------------------------------------------------------------|---------------------------|----------|
| IP rating: contacts / terminals                                                                |                           | IP 40/20 |
| <b>Actuator styles</b>                                                                         |                           |          |
| ▶ Pushbutton (standard)<br>No mounting brackets                                                | b                         |          |
| ▶ Pushbutton<br>with mounting brackets                                                         | c                         |          |
| ▶ Roller lever<br>No mounting brackets                                                         | e                         |          |
| ▶ Roller lever<br>with mounting brackets                                                       | a                         |          |
| ▶ Roller lever<br>with mounting brackets,<br>slotted holes                                     | as                        |          |
| ▶ Roller lever<br>with mounting brackets,<br>angled on one end                                 | d                         |          |
| ▶ Series<br>▶ Contact material<br>▶ Actuating and release force<br>▶ Blowouts (special design) | S800<br>*/10<br>*/40<br>L |          |
| <b>Terminal styles</b>                                                                         |                           |          |
| ▶ M3 screws with saddle clamp                                                                  | — *                       |          |
| ▶ Flat tabs 6.3x0.8                                                                            | 20                        |          |