

Ordering code

Example

S826 b 10/20/40 L

Series, contact configuration

S826	Dual changeover switch, wiping double-break contacts, positive opening operation, galvanically isolated contact bridges
S926	Same as S826 with improved resistance to chemicals, impact and extremes of temperature

Actuator styles

	Actuator	Mounting
b	Push button	no mounting plates
c	Push button	mounting plates
cs	Push button	mounting plates, slotted
e	Roller lever	no mounting plates
a	Roller lever	mounting plates
as	Roller lever	mounting plates, slotted
d	Roller lever	mounting plates, one angled

Contact material

*	Silver
10	Gold

Special design, optional

Magnetic blowout L

Actuating and release force

standard	+
reinforced	40

Terminals

M3 screws with saddle clamp	+
Flat tabs 6.3x0.8	20
Flat tabs 6.3x0.8, angled 90°	24
M3 screws with spring washer	30



Note:

This product catalogue comprises only stock items. For some variants minimum quantities apply. Please ask for conditions.

Special variants:

If you need a special variant of the switch, please do not hesitate to contact us. Maybe the type of switch you are looking for is among our many special designs. If not, we can also supply customized designs. In this case minimum quantities apply.

* No index

S826 / S926


S826 b / S926 b


Push button (standard), silver contacts and M3 screws with saddle clamp


S826 c / S926 c


Push button (standard), mounting brackets, silver contacts and M3 screws with saddle clamp


S826 b20 / S926 b20


Push button (standard), silver contacts and flat tabs 6.3 x 0.8


S826 a / S926 a

Roller lever, mounting brackets, silver contacts and M3 screws with saddle clamp


S826 e20 / S926 e20

Roller lever, silver contacts and flat tabs 6.3 x 0.8


S826 a L / S926 a L

Roller lever, mounting brackets, silver contacts, M3 screws with saddle clamp, and magnetic blowout

Parameter	Identification	Version
IP rating: contacts / terminals		IP40/20
Actuator styles		
▶ Push button (standard), no mounting plates	b	
▶ Push button, mounting plates	c	
▶ Push button, mounting plates, slotted	cs	
▶ Roller lever, no mounting plates	e	
▶ Roller lever, mounting plates	a	
▶ Roller lever, mounting plates, slotted	as	
▶ Roller lever, mounting plates, slotted, one angled	d	
▶ Series	S826	
▶ Contact material	* / 10	
▶ Actuating and release force	* / 40	
▶ Magnetic blowout (special design)	L	
Terminal styles		
▶ M3 screws with saddle clamp	— *	
▶ Flat tabs 6.3x0.8	20	
▶ Flat tabs 6.3x0.8, angled 90°	24	
▶ M3 screws with spring washer	30	