

Al-Cu kablovske papučice za gnječenje

Koriste se za završavanje Al provodnika i prelaz na Cu šinu. Izrađene su pre SRPS N.F4.101.

Kodni broj	Oznaka mm ² /Vijak M	d ₁	d ₂	d ₃	L ₁	L ₂	Broj presovanja meh./hidr.	Pakovanje kom	Težina g/100kom
		mm	mm	mm	mm	mm			
1901608	FACP-16/8	8,5	5,5	11,0	53,0	16,5	4-2	100	1,20
1902508	FACP-25/8	8,5	6,8	12,0	53,0	16,5	4-2	100	1,55
1903508	FACP-35/8	8,5	8,0	14,0	57,5	18,5	5-2	100	1,75
1903510	FACP-35/10	10,5	8,0	14,0	57,5	18,5	5-2	100	1,75
1903512	FACP-35/12	13,0	8,0	14,0	57,5	18,5	5-2	100	1,75
1905008	FACP-50/8	8,5	10,0	15,6	66,5	20,5	5-2	100	2,50
1905010	FACP-50/10	10,5	9,3	15,6	66,5	20,5	5-2	100	2,50
1907010	FACP-70/10	10,5	11,0	18,0	72,0	24,5	6-3	100	3,40
1907012	FACP-70/12	13,0	11,0	18,0	72,0	24,5	6-3	100	3,60
1909510	FACP-95/10	10,5	13,1	22,0	88,0	30,3	6-3	100	5,50
1909512	FACP-95/12	13,0	13,1	22,0	88,0	30,3	6-3	100	5,50
1912010	FACP-120/10	10,5	15,0	22,0	104,0	30,7	6-3	50	6,00
1912012	FACP-120/12	13,0	15,0	22,0	104,0	30,7	6-3	50	6,00
1915012	FACP-150/12	13,0	16,9	25,5	117,5	35,7	6-3	50	9,60
1915016	FACP-150/16	17,0	16,9	25,5	117,5	35,7	6-3	50	9,60
1918512	FACP-185/12	13,0	18,0	28,0	121,5	37,8	6-3	25	12,34
1918516	FACP-185/16	17,0	18,0	28,0	121,5	37,8	6-3	25	12,34
1924012	FACP-240/12	13,0	21,0	32,0	140,0	44,0	8-3	25	18,28
1924016	FACP-240/16	17,0	21,0	32,0	140,0	44,0	8-3	25	18,28
1930012	FACP-300/12	13,0	23,5	35,5	159,0	48,6	8-3	25	25,50
1930016	FACP-300/16	17,0	23,5	35,5	159,0	48,6	8-3	25	25,50